

18-4 SUPPLEMENT – 1986 MODEL

Item	ZX900-A3
Front tire: Type	Tubeless
Size	120/80V16-V250, (C) (U) 120/80V16
Rear tire: Type	Tubeless
Size	130/80V18-V250, (C) (U) 130/80V18
Front suspension: Type	Telescopic fork (pneumatic)
Wheel travel	140 mm
Rear suspension: Type	Swing arm (uni-trak)
Wheel travel	115 mm
Brake type: Front	Dual disc
Rear	Single disc
Electrical Equipment:	
Battery	12 V 14 Ah
Headlight: Type	Semi-sealed beam
Bulb	12 V 60/55 W (quartz-halogen)
Tail/brake light	12 V 5/21 W x2, (C) (SA) (U) 12 V 8/27 W x2
Alternator: Type	Three-phase AC
Rated output	25 A @6,000 r/min (rpm), 14 V
Voltage regulator: Type	Short-circuit

Specifications subject to change without notice, and may not apply to every country.

- (A) : Australian Model
- (C) : Canadian Model
- (Cal) : California Model
- (F) : French Model
- (I) : Italian Model
- (S) : Swiss Model
- (SA) : South African Model
- (Swe) : Swedish Model
- (U) : US Model
- (WG) : West German Model